

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 6579 (1981): Coarse Aggregate for Water Bound Macadam
[CED 6: Stones]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 6579 - 1981
(Reaffirmed 2008)

Indian Standard

**SPECIFICATION FOR
COARSE AGGREGATE FOR WATER
BOUND MACADAM
(*First Revision*)**

Third Reprint JULY 1999

UDC 666.972.123:625.863.2

© Copyright 1981

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

SPECIFICATION FOR COARSE AGGREGATE FOR WATER BOUND MACADAM (*First Revision*)

Stones Sectional Committee, BDC 6

<i>Chairman</i>	<i>Representing</i>
SHRI B. RAMACHANDRAN	Geological Survey of India
<i>Members</i>	
SHRI S. R. PRADHAN (<i>Alternate to</i> Shri B. Ramachandran)	
SHRI K. K. AGRAWALA	Builders' Association of India
SHRI K. K. MADHOK (<i>Alternate</i>)	
SHRI S. K. BANERJEE	National Test House, Calcutta
SHRI P. R. DAS (<i>Alternate</i>)	
SHRI R. K. BANSAL	Delhi Marble Dealers' Association, New Delhi
SHRI J. K. CHARAN	Engineer-in-Chief's Branch (Ministry of Defence)
SHRI K. KAMLANATHAN (<i>Alternate</i>)	
CHIEF ARCHITECT	Central Public Works Department, New Delhi
CHIEF ENGINEER (B & R)	Public Works Department, Government of Rajasthan, Jaipur
SHRI Y. N. DAVE	Department of Geology & Mining, Government of Rajasthan, Udaipur
SHRI R. G. GUPTA (<i>Alternate</i>)	
DEPUTY DIRECTOR (RESEARCH), PWD RESEARCH INSTITUTE, LUCKNOW	Public Works Department, Government of Uttar Pradesh, Lucknow
DR M. P. DHIR	Central Road Research Institute, New Delhi
DR N. B. LAL (<i>Alternate</i>)	
DIRECTOR (CSMRS)	Central Water Commission, New Delhi
DEPUTY DIRECTOR (CSMRS) (<i>Alternate</i>)	
DIRECTOR, GERI, VADODARA	Public Works Department, Government of Gujarat, Vadodara
SHRI M. K. GUPTA	Himalayan Tiles and Marble Pvt Ltd., Bombay
DR IQBAL ALI	Engineering Research Laboratories, Government of Andhra Pradesh, Hyderabad
SHRI G. RAMAKRISHNA (<i>Alternate</i>)	

(*Continued on page 2*)

© Copyright 1981

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI R. C. JAIN	Ministry of Shipping & Transport (Roads Wing), New Delhi
DR A. K. LAHIRI	Rajasthan State Granites and Marble Ltd, Jodhpur
SHRI K. VIKRAM (Alternate)	
SHRI R. G. LIMAYE	Indian Institute of Technology, Bombay
DR G. S. MEHROTRA	Central Building Research Institute, Roorkee
DR DINESH CHANDRA (Alternate)	
SHRI PREM SWARUP	Department of Geology & Mining, Government of Uttar Pradesh, Lucknow
SHRI A. K. AGARWAL (Alternate)	
DR A. V. R. RAO	National Buildings Organization, New Delhi
SHRI J. SEN GUPTA (Alternate)	
RESEARCH OFFICER, MERI, NASIK	Irrigation & Power Department, Government of Maharashtra, Bombay
SUPERINTENDING ENGINEER (DESIGNS)	Public Works & Electricity Department, Govern- ment of Karnataka, Bangalore
SUPERINTENDING ENGINEER (DESIGNS)	Public Works Department, Government of Tamil Nadu, Madras
DEPUTY CHIEF ENGINEER (I & D) (Alternate)	
SUPERINTENDING ENGINEER (PLANNING CIRCLE)	Public Works Department, Government of West Bengal, Calcutta
SHRI G. RAMAN, Director (Civ Engg)	Director General, ISI (<i>Ex-officio Member</i>)

Secretary

SHRI S. SENGUPTA
Assistant Director (Civ Engg), ISI

AMENDMENT NO. 1 OCTOBER 1996
TO
IS 6595 (Part 1) : 1993 HORIZONTAL
CENTRIFUGAL PUMPS FOR CLEAR, COLD WATER
PART 1 AGRICULTURAL AND RURAL WATER SUPPLY
PURPOSES — SPECIFICATION

(Second Revision)

[Page 2, clause 8.1(a)] — Substitute the following for the existing matter:

- ‘a) The pump shall be capable to operate without overloading the prime-mover in the specified head range. However, the head range shall be not less than minimum +5 percent and minimum -15 percent of rated duty point head up to 20 m. Above 20 m duty point head, the prime-mover shall not overload between duty point and minimum -3 m head.’

(HMD 20)

Reprography Unit, BIS, New Delhi, India

AMENDMENT NO. 2 OCTOBER 2000
TO
IS 6595 (PART 1) : 1993 HORIZONTAL CENTRIFUGAL
PUMPS FOR CLEAR, COLD WATER
PART 1 AGRICULTURAL AND RURAL WATER SUPPLY
PURPOSES — SPECIFICATION

(Second Revision)

(Page 3, Fig. 1) — Insert the following Note:

'NOTE — Efficiency of the pumps having declared duty point beyond the efficiency lines on either side may be declared by the manufacturer and applicable tolerance applied. Where the point lies in between the efficiency lines, the higher value be taken as minimum efficiency.'

(Page 4, Fig. 2) — Insert the following Note:

'NOTE — Efficiency of the pumps having declared duty point beyond the efficiency lines on either side may be declared by the manufacturer and applicable tolerance applied. Where the point lies in between the efficiency lines, the higher value be taken as minimum efficiency.'

(ME 20)

Indian Standard

SPECIFICATION FOR COARSE AGGREGATE FOR WATER BOUND MACADAM

(*First Revision*)

0. FOREWORD

0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 27 February 1981, after the draft finalized by the Stones Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 Water bound macadam (WBM) is a common item for highway construction. The coarse aggregates, accounting for nearly three-fourths of the volume and mass of WBM, may be said to be the main constituent. Many a time, an engineer-in-charge is faced with the problem of selecting the coarse aggregate for WBM from several alternative materials available. If the minimum physical requirements of such aggregates could be indicated, selection of the appropriate material would be easy. With this aspect in view, this standard has been prepared to lay down the requirements of coarse aggregates for WBM construction.

0.2.1 This standard was first published in 1972. It is being revised to incorporate improvements found necessary in the light of the usage of the standard and the suggestions made by various bodies implementing it. In this revision, a number of changes have been incorporated, the most important being the adoption of the WBM aggregates for construction of sub-base course also. The requirement of abrasion value, impact value and flakiness index of such aggregates for use as sub-base has been added and the size and grading of the WBM aggregates modified, depending on the sieve designation of IS : 460 (Part I)-1978*. A requirement for water absorption has also been included.

0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960†. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Specification for test sieves; Part I Wire cloth test sieves (*second revision*).

†Rules for rounding off numerical values (*revised*).

1. SCOPE

1.1 This standard specifies the quality, physical properties and grading of coarse aggregates suitable for use in WBM construction.

2. MATERIALS

2.1 The coarse aggregates used for WBM construction shall be any one of the following:

- a) Crushed or broken rock,
- b) Crushed or broken slag, and
- c) Broken brick aggregate.

2.1.1 Natural aggregates (like *KANKAR*, laterite, etc) other than mentioned in 2.1 may also be used.

3. QUALITY

3.1 The coarse aggregates from natural sources shall be hard and durable. They shall be free from excessive flat, elongated, soft or disintegrated particles, dirt and other similar sources of weakness.

3.2 The coarse aggregates of slag shall be made from air-cooled blast furnace slag and shall not contain glassy material exceeding 20 percent and shall not weigh less than 1 120 kg/m³. They shall be dense, of angular shape and shall be free from dirt and other similar sources of weakness.

3.3 The broken brick aggregate shall be made out of well burnt bricks (see IS : 1077-1976*). It shall be free from underburnt particles, dust and other foreign matter.

4. SIZE AND GRADING

4.1 The size and grading of the coarse aggregates shall be as specified in Table 1.

5. PHYSICAL REQUIREMENTS

5.1 Abrasion (Los Angeles) Value — The abrasion value of the coarse aggregates when tested in accordance with the method laid down in IS : 2386 (Part IV)-1963† shall not be more than 40 percent for wearing surface, 50 percent for base course and 60 percent for sub-base course.

*Specification for common burnt clay building bricks (*third revision*).

†Methods of test for aggregates for concrete: Part IV Mechanical properties.

TABLE 1 SIZE AND GRADING OF COARSE AGGREGATES

(Clause 4.1)

GRADING No.	SIEVE DESIGNATION [<i>see</i> IS : 460 (PART I)-1978*]	PERCENTAGE PASSING THE SIEVE BY MASS
(1)	(2)	(3)
	mm	
1	106	100
	75	55 to 80
	63	25 to 60
	37.5	0 to 15
	19	0 to 5
2	75	100
	63	90 to 100
	53	50 to 80
	37.5	0 to 15
	19	0 to 5
3	63	100
	53	95 to 100
	37.5	30 to 65
	19	0 to 10
	11.2	0 to 5

NOTE — For coarse aggregates susceptible to degradation during rolling, the above grading may not hold good.

*Specification for test sieves: Part I Wire cloth test sieves (*second revision*).

5.2 Flakiness Index — The flakiness index of the coarse aggregates when tested in accordance with the method given in IS : 2386 (Part I)-1963* shall not be more than 15 percent. The flakiness index may be judiciously adjusted when the material is to be used in sub-base or when significant degradation is expected under rolling.

NOTE — The requirement of flakiness index shall be enforced only in the case of crushed broken stone and crushed slag.

5.3 Impact Value — The impact value of the aggregates when determined in accordance with the method given in IS : 2386 (Part IV)-1963† and IS : 5640-1970‡ shall not be more than 30 for wearing surface, 40 for base course and 50 for sub-base course.

NOTE — Aggregates like brick, KANKAR and laterite shall be tested for impact value under wet condition in accordance with the methods given in IS : 5640-1970‡.

*Methods of test for aggregates for concrete: Part I Particle size and shape.

†Methods of test for aggregates for concrete: Part IV Mechanical properties.

‡Methods of test for determining aggregates impact value of soft coarse aggregates.

5.4 Water Absorption — The water absorption of the aggregates when tested in accordance with the method given in IS : 2386 (Part III)-1963* shall not be more than 1.5 percent for wearing surface, base and sub-base course in the areas where the aggregates are subjected to freezing and thawing and shall not be more than 2 percent in other areas.

5.5 Soundness — The soundness of the aggregates when tested in accordance with the method given in IS : 2386 (Part V)-1963† shall satisfy the following requirements:

- a) Loss with sodium sulphate (5 cycles) : 20 percent *Max*
- b) Loss with magnesium sulphate (5 cycles) : 30 percent *Max*

NOTE — The aggregate shall be tested for soundness only when it has to undergo alternate freezing and thawing.

6. SAMPLING AND CRITERIA FOR CONFORMITY

6.1 The procedure of sampling and the criteria for conformity shall be as given in IS : 2430-1969‡.

7. SUPPLIER'S CERTIFICATE AND COST OF TESTS

7.1 The supplier shall satisfy himself that the material supplied conforms to the requirements of this standard and, if requested, shall furnish a certificate to this effect to the purchaser or his representative.

7.2 If the purchaser or his representative requires independent tests to be made, the sample for such tests shall be taken before or immediately after delivery at the option of the purchaser or his representative, and the tests shall be carried out in accordance with this standard and on the written instructions of the purchaser or his representative.

7.3 The supplier shall supply, free of charge, the material required for tests.

7.4 The cost of the tests carried out under 7.2 shall be borne as follows:

- a) By the supplier, if the results show that the material does not comply with this standard; and
- b) By the purchaser, if the results show that the material complies with this standard.

*Methods of test for aggregates for concrete : Part III Specific gravity, density, voids, absorption and bulking.

†Methods of test for aggregates for concrete : Part V Soundness.

‡Methods for sampling of aggregates for concrete.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402

Fax 91 11 3234062, 91 11 3239399, 91 11 3239382

Telegrams : Manaksanstha
(Common to all Offices)

Central Laboratory:

Plot No. 20/9, Site IV, Sahibabad Industrial Area, SAHIBABAD 201010

Telephone
8-77 00 32

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002	323 76 17
*Eastern : 1/14 CIT Scheme VII M, V.I.P. Road, Maniktolia, CALCUTTA 700054	337 86 62
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022	60 38 43
Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113	235 23 15
†Western : Manakalaya, E9 Behind Marol Telephone Exchange, Andheri (East), MUMBAI 400093	832 92 95

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001	550 13 48
‡Peenya Industrial Area, 1st Stage, Bangalore - Tumkur Road, BANGALORE 560058	839 49 55
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 462003	55 40 21
Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 751001	40 36 27
Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037	21 01 41
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	8-28 88 01
Savitri Complex, 116 G. T. Road, GHAZIABAD 201001	8-71 19 96
53/5 Ward No. 29, R. G. Barua Road, 5th By-lane, GUWAHATI 781003	54 11 37
5-8-58C, L. N. Gupta Marg, Nampally Station Road, HYDERABAD 500001	20 10 83
E-52, Chitaranjan Marg, C-Scheme, JAIPUR 302001	37 29 25
117/418 B, Sarvodaya Nagar, KANPUR 208005	21 68 76
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001	23 89 23
Patliputra Industrial Estate, PATNA 800013	26 23 05
T. C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034	6 21 17
NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010	52 51 71
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	32 36 35

*Sales Office is at 5 Chowringhee Approach, P. O. Princep Street, CALCUTTA 700072

27 10 85

†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007

309 65 28

‡Sales Office is at 'F' Block, Unity Building, Narashimaraaja Square, BANGALORE 560002

222 39 71